

BLADE FORCE™ 250

Combination Smoothbore Nozzle



Overview

The HEN® BLADE FORCE™ nozzle combines the power of a smoothbore nozzle with a solid linear BLADE™ stream, delivering both a tight, solid stream for penetration and a blade-like pattern for enhanced fire attack versatility and coverage. Flowing at 250gpm @ 45psi with just 89lbs of nozzle reaction. The BLADE FORCE™ sets the industry standard for low pressure PSI nozzles.

Features

- Solid tight pattern with large water droplets
- Works with ALL 2", 2.25", & 2.5" hoseline
- 250 GPM @ 45 PSI nozzle pressure
- Hard-coat anodized aluminum construction
- Available with 1.5" NH & 1.5" NPSH threads
- NFPA 1960/1964 compliant
- 5-Year Warranty

Specifications

	IMPERIAL	METRIC
Target Flow	250 gpm	940 lpm
Target Pressure	45 psi	3 bar
BLADE™ Pattern Angle	22°	22°
Weight	1.9 lb	0.86 kg
Length	7.2 in.	183 mm
Width	3.4 in.	86 mm

Flow Rates

PRESSURE PSI (BAR)	FLOW RATE GPM (LPM)
30 (2.1)	205 (776)
45 (3.1)	251 (951)
50 (3.4)	265 (1002)
60 (4.1)	290 (1098)
70 (4.8)	313 (1186)



**NFPA
COMPLIANT**