

# TIP FORCE™ 175

## Smoothbore Nozzle

### Overview

The HEN® TIP FORCE™ 175 nozzle delivers a smoothbore-like performance with a tight, solid stream, maximizing reach and penetration for effective fire suppression while maintaining the benefits of a pressure-managed nozzle. Flowing at 175gpm @ 45psi with just 60lbs of nozzle reaction. The TIP FORCE™ sets the industry standard for low pressure PSI nozzles.

### Specifications

	IMPERIAL	METRIC
Target Flow	175 gpm	660 lpm
Target Pressure	45 psi	3 bar
Weight	1.1 lb	0.50 kg
Length	6 in.	152.4 mm
Width	2.7 in.	69 mm



### Features

- Solid tight pattern with large water droplets
- Hard-coat anodized aluminum construction
- Available with 1.5" NH, 1.5" NPSH threads
- Full-time swivel
- NFPA 1960/1964 compliant
- 5-Year Warranty

### Flow Rates

PRESSURE PSI (BAR)	FLOW RATE GPM (LPM)
30 (2.1)	143 (541)
45 (3.1)	175 (663)
50 (3.4)	185 (699)
60 (4.1)	202 (765)
70 (4.8)	218 (827)



**NFPA  
COMPLIANT**